KARAKTERISTIK & SPESIFIKASI KINERJA

No	TYPE	KARAKTERISTIK	SPESIFIKASI KINERJA	ANALISA RESIKO ALAT	SPESIFIKASI KEMASAN
1	3011 D-ST	Sistem pengoperasian secara manual menggunakan 1 Crank 1 Cylinder (adjustable hi-lo secara manual dengan menggunakan crank dan manual back raise dengan menggunakan cylinder gas control)	Pengoperasian secara manual diputar dan ditekan pada handle untuk back raise	Cara penggunaan yang salah dan seringnya diputar crank akan cepat rusak, pemakaian yang lama akan menyebabkan kebocoran gas lift	CB/F K200/M150x3/K200 975 x 2350 x 170
		Sistem penguncian roda caster menggunakan sistem penguncian 4 (empat roda) Total lock caster dengan menggunakan pedal injak	Fungsi lock pada caster akan maksimal jika posisi bed diletakkan pada lantai datar	Posisi penempatan bed harus dalam kondisi permukaan lantai datar, karena bila diletakkan posisi miring maka fungsi lock pada akan caster akan cepat rusak	

CB 3011 D-ST

OPTIONS

FEATURES & PROCEDURES

Head/foot board panel dismantle

Head/foot board panel installation

OPERATION SYSTEM

A unique eye catching foldable crank is designed to give high-low bed adjustment.

Crank operation system

Back raise adjustment

CASTER OPERATION SYSTEM

Independent lock caster (one at front and one at back of the bed) provides stability and secure parking.